

FirstCall - 错误 #4085

3.0基站 Uu+Dd测试, APE4概率跑死

2025-09-18 10:49 - 白瑞朋

状态:	进行中	开始日期:	2025-09-18
优先级:	普通	计划完成日期:	
指派给:	白瑞朋	% 完成:	0%
类别:		预期时间:	0.00 小时
目标版本:		耗时:	0.00 小时
描述			
Uu+Dd测试, APE4概率跑死, 接入流程只跑到Msg5.			
PHY:基于dev_d2d_trunk_On_board_debug			
3.0基站: 192.168.2.30/192.168.2.32			

历史记录

#1 - 2025-09-18 10:51 - 白瑞朋

- 状态从新建变更为进行中

- 指派给被设置为白瑞朋

待复现问题, 再继续分析。

#2 - 2025-09-18 11:00 - 白瑞朋

- 主题从Uu+Dd测试, APE4概率跑死变更为3.0基站Uu+Dd测试, APE4概率跑死

#3 - 2025-09-18 12:14 - 白瑞朋

- 文件4-0-str.log已添加

#4 - 2025-09-18 12:22 - 白瑞朋

- 文件APE4挂.jpg已添加

#5 - 2025-09-18 14:01 - 白瑞朋

- 文件已删除(APE4挂.jpg)

#6 - 2025-09-18 14:02 - 白瑞朋

- 文件APE4挂.jpg已添加

PDU建立成功后, APE4核挂死。

```
addr = 0x8700068, len = 64
phy_addr=0x8700068, mmap_addr=0x8700000, len = 64
0x08700068: 0x00000157 0x00000157 0x00000157 0x00000157
0x08700078: 0x00000036 0x00000154 0x00000157 0x00000157
0x08700088: 0x00000000 0x0000002f 0x00000417 0x0000005a
0x08700098: 0x00000000 0x00000000 0x00000000 0x00000000
osp_dislay_phy_mem return ok!
root@driver:/home/B5gUe/phy# test_mem 0x8700068 64
addr = 0x8700068, len = 64
phy_addr=0x8700068, mmap_addr=0x8700000, len = 64
0x08700068: 0x00000159 0x00000159 0x00000159 0x00000159
0x08700078: 0x00000036 0x00000156 0x00000159 0x00000159
0x08700088: 0x00000000 0x00000030 0x0000041c 0x0000005a
0x08700098: 0x00000000 0x00000000 0x00000000 0x00000000
osp_dislay_phy_mem return ok!
root@driver:/home/B5gUe/phy# ifconfig
eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 192.168.2.121 netmask 255.255.255.0 broadcast 192.168.2.255
    ether 44:00:88:ff:f2:79 txqueuelen 1000 (Ethernet)
    RX packets 8872 bytes 760850 (743.0 KiB)
    RX errors 0 dropped 2458 overruns 0 frame 0
    TX packets 2125 bytes 462895 (452.0 KiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
    device interrupt 23 base 0x8000

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    loop txqueuelen 1000 (Local Loopback)
    RX packets 40 bytes 3840 (3.7 KiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 40 bytes 3840 (3.7 KiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

ue_uu: flags=469<UP,DEBUG,POINTOPOINT,RUNNING,NOARP,PROMISC> mtu 1500
    inet 60.60.0.100 netmask 255.255.255.0 destination 60.60.0.100
    unspec 00-00-00-00-00-00-00-00-00-00-00-00-00-00-00-00 txqueuelen 500 (UNSPEC)
    RX packets 0 bytes 0 (0.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 0 bytes 0 (0.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
```

APE4计数停止

pdu建立成功

文件

4-0-str.log	171 KB	2025-09-18	白瑞朋
APE4挂.jpg	393 KB	2025-09-18	白瑞朋